

Product Data Sheet: DC-Guard DACAiR

- Air duct with baffle to direct the air stream towards the visor to prevent fogging.
- Perfect vision reducing distortion or eye fatigue.
- Optical class 1 polycarbonate visor.
- Maximum protection against impacts thanks to its wide browguard extended to the rear covering not only the forehead.
- Low weight. The head unit weights just 620 g.
- Available: peel off visors to protect and extend the life of the visor.
- Certified CE EN 12941, class TH2, EN 166 3 9 B.




Ref: EQDACAIRDCG

SPARES / ACCESSORIES

- Headgear with airduct for DACAiR
- DC-Guard DACAiR face seal
- DACAiR sweatbands (pack of 2 units)
- PC visor with chinguard prepared for DACAiR
- Pack of 10 peel off visors for DC-Guard DACAiR

REFERENCES

- PA200S02
- DCGAFS
- PA200S05B
- IV30700CGDAC
- IV3070CGPO



Complete unit sold with 2 peel off disposable visors



The DC-Guard grinding shield with DACAiR PAPR is conform to the harmonized European Legislation 2016/425 and is certified according to the EN166 3 9 B and CE EN 12941, TH2 class standards

TECHNICAL FEATURES PAPR DACAiR

- Ligtweight and compact
- Air flow
- Filter type
- Battery
- Running time with fully charged battery

- Charging cycles: >350
- Assigned Protection Factor
- Noise level
- Certificate
- Warranty

- The complete unit (filter included) weights only 920 gr
- 180 or 220 litres / min
- Replaceable filter P R SL
- Li-ion 7.4 V / 5200 mAh
- At 180 l / min > 8 hours, at 220 l / min > 5 hours. Running time can be reduced
- Fast charging time: < 4 hours
- 500 (TH3) - 50 (TH2)
- Max. 69 to 74 dB(A) depending on head unit
- CE EN 12941 class TH2 or TH3 (depending on head unit).
- Battery: 6 months / PAPR: 1 year